

SPECIFICATIONS

Standard Features

FRAMEWORK

Structural steelwork painted one coat, high quality grey oxide primer.

CLADDING

P.V.C. coated box profile steel sheets, complete with all necessary flashings, fillers and fittings. No site cutting required.

TRANSLUCENT ROOF LIGHTS

Provide ample natural light. Approximately 10% of roof area.

SLIDING / PERSONNEL DOORS

Double leaf bi-parting steel framed doors, top hung, with security drop bolts and separate steel personnel door fitted to each gable end on 12m, 15m, 18m, 20m, 24m span buildings. On the 7.32m and 9m span buildings, the main door is fitted in one gable with a personnel door only in the other gable end.

Optional Features

CLADDING

Choice of P.V.C. paint coated finishes in a range of colours. Colour charts are available on request.

LININGS / INSULATION

By fibreglass material fixed between the exterior cladding and steel liner. Liner is painted bright white as standard.

RAINWATER GOODS

High quality P.V.C. guttering, downpipes and fittings.

PARTITIONS

Support steel work and cladding for internal divisions.

FIRE PROTECTION

1hour fire protection to walls and columns.

ROLLER SHUTTER DOORS, ADDITIONAL SLIDING DOORS AND PERSONNEL DOORS

